


MDTE Series




FEATURES



- So saturation
- High current,low DCR,high efficiency
- Very low acoustic noise and very low leakage flux noise
- High reliability
- 100% Lead(Pb)-Free and RoHS compliant
- Operating temperature -55~+125 ℃ (Including self - temperature rise)
- Quantity: 450pcs

APPLICATION

- Note PC power sys
- DC/DC converter




Part No	Inductance @ 100KHz/0.1V	Tolerance	Current Typ.	Current Max.	Temperature Rise Current Typ.	DC Resistance Max.	D
MDTE8080-1R8M	1.80	±20%	28.0	24.0	24.0	4.0	7.2±0.3
MDTE8080-2R2M	2.20	±20%	25.0	22.0	21.5	4.3	7.2±0.3
MDTE8080-3R3M	3.30	±20%	23.0	20.0	18.0	7.3	6.9±0.3
MDTE8080-4R7M	4.70	±20%	19.0	17.0	14.6	9.8	6.9±0.3
MDTE8080-6R8M	6.80	±20%	14.5	12.5	11.3	14.3	6.9±0.3
MDTE8080-100M	10.0	±20%	11.0	10.0	8.7	22.9	6.9±0.3



°C
°C
°C

:

MDTE8080	9.4±0.1	8.9±0.1	1.5±0.1	4.0±0.1	16.0±0.1	24.0±0.3	8.5±0.1	1.75±0.1	0.35±0.05



The peel force of top cover tape shall be between 0.1 to 1.3 N

:

